


HEX FLAT SOCKET HEAD CAP SCREWS



Nominal Diameter		D		HD		H		KS		KE
		Body Diameter		Head Diameter		Head Height		Hexagon Key Size		Key Engagement
				Theoretical Sharp Max	Abs. Min	Reference	Flushness Tolerance			
Fractional	Decimal	Max	Min					Nom	Min	
# 0	0.0600	0.0600	0.0568	0.138	0.117	0.044	0.006	0.035	0.025	
# 1	0.0730	0.0730	0.0695	0.168	0.143	0.054	0.007	0.050	0.031	
# 2	0.0860	0.0860	0.0822	0.197	0.168	0.064	0.008	0.050	0.038	
# 3	0.0990	0.0990	0.0949	0.226	0.193	0.073	0.010	1/16 0.062	0.044	
# 4	0.1120	0.1120	0.1075	0.255	0.218	0.083	0.011	1/16 0.062	0.055	
# 5	0.1250	0.1250	0.1202	0.281	0.240	0.090	0.012	5/64 0.078	0.061	
# 6	0.1380	0.1380	0.1329	0.307	0.263	0.097	0.013	5/64 0.078	0.066	
# 8	0.1640	0.1640	0.1585	0.359	0.311	0.112	0.014	3/32 0.094	0.076	
#10	0.1900	0.1900	0.1840	0.411	0.359	0.127	0.015	1/8 0.125	0.087	
1/4	0.2500	0.2500	0.2435	0.531	0.480	0.161	0.016	5/32 0.156	0.111	
5/16	0.3125	0.3125	0.3053	0.656	0.600	0.198	0.017	3/16 0.188	0.135	
3/8	0.3750	0.3750	0.3678	0.781	0.720	0.234	0.018	7/32 0.219	0.159	
7/16	0.4375	0.4375	0.4294	0.844	0.781	0.234	0.018	1/4 0.250	0.159	
1/2	0.5000	0.5000	0.4919	0.938	0.872	0.251	0.018	5/16 0.312	0.172	
5/8	0.6250	0.6250	0.6163	1.188	1.112	0.324	0.022	3/8 0.375	0.220	
3/4	0.7500	0.7500	0.7406	1.438	1.355	0.396	0.024	1/2 0.500	0.220	
7/8	0.8750	0.8750	0.8647	1.688	1.604	0.468	0.025	9/16 0.562	0.248	
1	1.0000	1.0000	0.9886	1.938	1.841	0.540	0.028	5/8 0.625	0.297	
1-1/8	1.1250	1.1250	1.1086	2.188	2.079	0.611	0.031	3/4 0.750	0.325	
1-1/4	1.2500	1.2500	1.2336	2.438	2.316	0.683	0.035	7/8 0.875	0.358	
1-3/8	1.3750	1.3750	1.3568	2.688	2.553	0.755	0.038	7/8 0.875	0.402	
1-1/2	1.5000	1.5000	1.4818	2.938	2.791	0.827	0.042	1 1.000	0.435	

Note: L = Length of Screw