POWDER ACTUATED FASTENING TOOLS (PAT)



BP-361

.27cal Automatic Powder Actuated Tool



Technical Data


Dimensions: 16-1/8" x 2-1/8" x 6.1/2"

Weight: 5.0lb

Fastener Type: Flat & dome head pins or threaded studs

Fastener length: 1/2" - 1-7/8"

Load Type: .27cal. (6.8 x 11mm) strip loads



BUEPOINTFASTENERS

Applications and Advantages

- ° Commercial and residential construction
- Drywall track
- ° Conduit clips fastening
- ° Electrical fixtures
- Duct straps
- Wood to steel
- Wood to concrete
- Metal track
- ° Concrete forming
- Door frames
- Perimeter plates
- Furring Channel
- ° Brick Ties
- Automatic piston return and powder loads advance
- Variable level adjustment
- Reduces noise level

BP-361M

.27cal Automatic Tool w/ Magazine



Technical Data

Dimensions: 16-1/4" x 2-1/8" x 8-3/4"
Weight: 5.4lb (with magazine)
Fastener Type: Flat and dome collated pins

Fastener length: 1/2" - 1-1/4"

Load Type: .27cal. (6.8 x 11mm) strip loads



Yellow/4

Applications and Advantage

- ° Commercial and residential construction
- Drywall track
- Electrical fixtures
- Duct straps
- Wood to steel
- Wood to concrete
- Metal track
- ° Concrete forming
- Door forming
- ° Perimeter plates
- ° Furring channel
- Brickties
- Automatic piston return
- Automatic pins and powder loads advance
- Variable level adjustment
- Reduces noise level



POWDER ACTUATED FASTENING TOOLS (PAT)



BP-302A

.27cal Noise Canceling Semi-Automatic
Powder Actuated Tool w/ Power Adjuster

* Specially designed for all day fastening in occupied spaces such as Hospitals, Schools, Offices etc.





Technical Data

Weight: 5.5 lbs **Length:** 13-3/4" **Pin Type:** .300" /.315" /8mm head pin,

1/4" - 20 threaded stud

Pin Length: 1/2" to 2-1/2" total length **Load Type:** .27cal. 10 load strip.

Brown/2 Green/3 Yellow/4 Red/5 Purple/6

Applications:

- Concrete forming
- Wood to concrete/steel
- Electrical fixture to concrete/ steel
- Conduit clip to concrete
- Commercial & residential construction

Advantages:

- Adjustable power levels
- · Very low noise
- Shoots up to full 2-1/2" pins
- · High strength durable piston

Suitable Base Materials:

- Normal-weight concrete
- · Concrete masonry
- Steel

BP-301C

.27cal Semi-Automatic Powder Actuated Tool



Technical Data

Weight: 5 lbs Length: 13-5/8" Pin Type: .300" /.315" /8mm head pin,

1/4" - 20 threaded stud

Pin Length: 1/2" to 2-1/2" total length **Load Type:** .27cal. 10 load strip.

Brown/2 Green/3 Yellow/4 Red/5

Applications:

- · Concrete forming
- Wood to concrete/steel
- Electrical fixture to concrete/ steel
- Conduit clip to concrete
- Commercial & residential construction

Advantages:

- Most popular and reliable tool in the market
- Most parts inter-changeable with other brand tools

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel

Purple/6

BP-303A

.27cal Semi-Automatic Powder Actuated Tool
w/ Power Adjuster



Technical Data

Weight: 5 lbs Length: 14"
Pin Type: .300" /.315" /8mm head pin,

1/4" - 20 threaded stud

Pin Length: 1/2" to 3" total length Load Type: .27cal. 10 load strip.

Brown/2 Green/3 Yellow/4 Red/5 Purple/6

Applications:

- Concrete forming
- Wood to concrete/steel
- Electrical fixture to concrete/ steel
- Conduit clip to concrete
- Commercial & residential construction

Advantages:

- Adjustable power levels
- Shoots up to full 3" pins
- High strength durable piston
- Protective rubber front barrel sleeve for user protection

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel

POWDER ACTUATED FASTENING TOOLS (PAT)

BP-307S

.22cal Single Shot Powder Actuated Tool



Technical Data

Weight: 4.2 lbs Length: 13-3/4" Pin Type: .300" /.315" /8mm head pin,

1/4" - 20 threaded stud

Pin Length: 1/2" to 3" total length Load Type: .22cal. neck down single shot

Brown/2 Green/3 Yellow/4 Red/5

Advantages:

- Light Weight Durable Design w/ Rubber Cushion Grip
- Automatic Cartridge Ejection
- Replaceable Piston Buffer for Overdrive Protection
- Replaceable Piston and Piston Stop Guide
- Meets or Exceeds OSHA/ ANSI A 10.3/ PATMI Safety Standards

RULEPOINT

- Drywall Track to Concete/ Steel
- Electrical fixture to Concrete/ Steel
- Wood Furring Strips/ Perimeter Plates to Concrete
- Wood Framing Plates to Steel
- Hooks, Hangers and Cable ties to

Concrete/ Steel

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel

BP-307 .22cal Powder Actuated Tool



Technical Data

Weight: 4 lbs Length: 13.19" Pin Type: .300" /.315" /8mm head pin,

1/4" - 20 threaded stud

Pin Length: 1/2" to 3" total length Load Type: .22cal. neck down load.

Brown/2

Green/3

Yellow/4 Red/5

Applications:

- Track to floor
- Wood to concrete/steel
- Electrical fixture to concrete/ steel
- Conduit clip to concrete
- Commercial & residential construction

Suitable Base Materials:

- Normal-weight concrete
 - Concrete masonry
 - Steel

BP-H01

.22cal Single Shot Hammer Activated Tool







Technical Data

Weight: 2.2 lbs Length: 13-9/16" **Pin Type:** .300" /.315" /8mm head pin,

1/4" - 20 threaded stud Pin Length: 1/2" to 3" total length Load Type: .22cal. neck down single shot

Brown/2 Green/3 Yellow/4 Red/5

Advantages:

- Light Weight Durable Design w/ Rubber Cushion Grip
- Automatic Cartridge Ejection
- Replaceable Piston Buffer for Overdrive Protection
- Replaceable Piston and Piston Stop Guide
- Meets or Exceeds OSHA/ ANSI A 10.3/ PATMI Safety Standards

Applications:

- Conduit clip to concrete/ Steel
- Drywall Track to Concete/ Steel
- Electrical fixture to Concrete/ Steel
- Wood Furring Strips/ Perimeter Plates to Concrete
- Wood Framing Plates to Steel
- Hooks, Hangers and Cable ties to Concrete/ Steel

Suitable Base Materials:

- Normal-weight concrete
- Concrete masonry
- Steel







*Enhanced strips are good for heavy duty and full automatic fastening tools















Model No.	Package/Qty	Size	Description	Color	Power	Power Level
27ES11L6	100 10000	6.8 x 11	x 11 .27cal Enhanced strip loads	Purple	Strongest	6
27ES11L5	100 10000	(mm)		Red	Strong	5
27LS11L5	100			Red	Strong	5
27LS11L4	100	6.8 x 11		Yellow	Medium	4
27LS11L3	100 100 10000	(mm)	.27cal long strip loads	Green	Low	3
27LS11L2	10000			Brown	Lowest	2
25SS10L5	100 10000			Red	Strong	5
25SS10L4	10000	6.3 x 10		Yellow	Medium	4
25SS10L3	10000	(mm)	.25cal strip loads	Green	Low	3
25SS10L2	10000			Brown	Lowest	2
25MD10L5	10000			Red	Strong	5
25MD10L4	10000 10000 10000	6.3 x 10	.25cal metal disc loads	Yellow	Medium	4
25MD10L3	10000	(mm)		Green	Low	3
25MD10L2	100			Brown	Lowest	2
22SGNDL5	100		.22cal neck down single shot loads	Red	Strongest	5
22SGNDL4	100			Yellow	Strong	4
22SGNDL3	100	5.6 x 16		Green	Medium	3
22SGNDL2	100	(mm)		Brown	Low	2
22SGNDL1	100			Gray	Lowest	1
22L4B	100 10000		.22cal neck down single shot loads, brass case	Yellow	Strong	4
22SGSWL6	100 100 10000		one reade, prace eace	Purple	Strong	6
22SGSWL5	100	5.6 x 15	.22cal straight wall single shot	Red	Medium	5
22SGSWL4	10000	(mm)	loads	Yellow	Low	4
22SGSWL3	10000			Green	Lowest	3
22SL6B	100 100 10000			Purple	Strong	6
22SL5B	10000	5.6 x 15	.22cal straight wall single shot	Red	Medium	5
22SL4B	10000	(mm)	loads, Brass casing for Ninja tool	Yellow	Low	4
22SL3B	10000			Green	Lowest	3
27SGL3LB	10000			Purple	Strong	6
27SGL4LB		6.8 x 18	.27cal (6.8*18) single shot	Red	Medium	5
27SGL5LB		(mm)	long loads, brass case	Yellow	Low	4
27SGL6LB				Green	Lowest	3

Actual Embedment Drive Pins















Advantages

- ° The Blue Point .157" diameter shank Actual Embedment (AE) pin is sized to provide actual embedment depths in track or clips up to 14 gauge (2mm).
- Assured to meet the required embedment depths into concrete or steel without compensating for the track or clip thickness.
- The pin heads are stamped for easy identification before and after installation.
- Choose the correct pins confidently For example, using the 1" AE pin, the actual embedment depth into the concrete is 1". There is no longer a need to use a 1-1/4" pin to assure a 1" embedment.
- Nominal .315" head diameter, thick heavy duty head provide true guidance for better drivability.
- Available in single shot and strip pin applications

Single Drive Pins

	Item No.	Shank Length	Description	Package/ Qty
A	PD157-12PKAE	1/2"	.315" head, .157" dia. shank knurled AE pin w/ plastic washer	100/1000/5000
	PD157-12FKAE	1/2"	.315" head, .157" dia. shank knurled AE pin w/ rubber flute	100/1000/5000
	PD157-34FAE	3/4"		100/1000/5000
A	PD157-100FAE	1"	.315" head dia., .157" dia. shank	100/1000
A	PD157-114FAE	1-1/4"	AE pin w/ rubber flute	100/1000
A	PD157-112FAE	1-1/2"		100/1000

Collated Drive Pins

	Item No.	Shank Length	Description	Package/ Qty
A	PDC157-12KAE	1/2"	.315" head, .157" dia. shank knurled AE pin w/ plastic strip	100/1000/5000
	PDC157-34AE	3/4"		100/1000/5000
	PDC157-100AE	1"	.315" head dia., .157" dia. shank	100/1000
	PDC157-114AE	1-1/4"	AE pin w/ plastic strip	100/1000
	PDC157-112AE	1-1/2"		100/1000

*.315" Dia. Head, .157" dia. Shank Premium Steel Pin

Item No.	Shank Length	Description	Box	Case	Master Box
PP58SG	5/8"	Slim groove shank with plastic washer	100	1000	5000

*.300" Dia. Head, .181"/.150" Step Shank dia. Premium Pin

Item No.	Shank Length	Description	Box	Case	Master Box
PP181S-178F	1-7/8"	.300" dia. head, .181"150" step shank premium pin.	100	1000	5000





.300" Dia. Head, .157" Dia. Shank Drive Pins

Plain Pins:

Item No.	Shank Length	Description	Box	Case	Master Box
PD157-12PK	1/2"	Knurled Shank with plastic washer	100	1000	5000
PD157-12FK	1/2"	Knurled Shank with rubber flute	100	1000	5000
PD157-58F	5/8"	Smooth shank with rubber flute	100	1000	5000
PD157-34F	3/4"	Smooth shank with rubber liute	100	1000	5000
PD157-34FB	3/4"	Smooth shank with rubber flute/bulk	-	1000	5000
PD157-78F	7/8"		100	1000	5000
PD157-100F	1"		100	-	1000
PD157-114F	1-1/4"		100	-	1000
PD157-112F	1-1/2"		100	-	1000
PD157-158F	1-5/8"		100	-	1000
PD157-134F	1-3/4"	Smooth shank with rubber flute	100	-	1000
PD157-178F	1-7/8"		100	-	1000
PD157-200F	2"		100	-	1000
PD157-214F	2-1/4"		100	-	1000
PD157-212F	2-1/2"		100	-	1000
PD157-300F	3"		100	-	1000





Collated Drive Pins:

Item No.	Shank Length	Description	Box	Case			
PDC157-12K	1/2"	Knowled about with pleatic atric	100	1000			
PDC157-34K	3/4"	Knurled shank with plastic strip	100	1000			
PDC157-34	3/4"		100	1000			
PDC157-78	7/8"		100	1000			
PDC157-100	1"		100	1000			
PDC157-114	1-1/4"	Smooth shank with plastic strip	100	1000			
PDC157-112	1-1/2"	Smooth shank with plastic strip	100	1000			
PDC157-200	2"		100	1000			
PDC157-212	2-1/2"		100	1000			
PDC157-278	2-7/8"		100	1000			



Washer Pins:

Item No.	Shank Length	Description	Box	Case
PD157-114W	1-1/4"		100	1000
PD157-112W	1-1/2"	With 1" dia. metal round washer	100	1000
PD157-212W	2-1/2"		100	1000
PD157-300W	3"		100	1000



Heavy Mechanical Galvanized Washer Pins:

Item No.	Shank Length	Description	Box	Case
PD157-200WMG	2"	.300" dia. head, .157" dia. shank	100	1000
PD157-212WMG	2-1/2"	drive pins w/1" dia. metal round	100	1000
PD157-278WMG	2-7/8"	washer - Heavy mechanical galvanized for	100	1000
PD157-300WMG	3"	pressure-treated wood	100	1000



Angle Clip Pins:

Item No.	Shank Length	Description	Box	Case
PD157-100C90	1"		100	1000
PD157-100C90B] '	M/H- 000	-	1000
PD157-114C90	4 4/411	With 90° angle clip	100	1000
PD157-114C90B	1-1/4"		-	1000
PD157-78THC90	7/8"	With Top hat and 90° angle clip	100	1000
PD157-78THC90B	770		-	1000
PD157-78HNC	7/8"		100	1000
PD157-100HNC	1"	With Top hat and Ninja Clip	100	1000
PD157-114HNC	1-1/4"		100	1000



.300" Dia. Head, .145" Dia. Shank Drive Pins

Plain Pins:

Item No.	Shank Length	Description	Box	Case	Master Box
PD13F10K	1/2"	Knurled shank pin with flute	100	1000	5000
PD13PK	1/2"	Knurled shank pin with plastic washer	100	1000	5000
PD16F10K	5/8"	Knurled shank pin with flute	100	1000	5000
PD19F10	3/4"	Smooth shank pin with flute	100	1000	5000
PD19PFBL	3/4"	Pinch point track pin (black)	-	1000	5000
PD19FBLB	3/4"	Track pin (black) with flute/ bulk	-	1000	5000
PD19PFBLB	3/4"	Pinch point track pin (black)/ bulk	-	1000	5000
PD22F10	7/8"		100	1000	5000
PD25F10	1"		100	1000	5000
PD32F10	1-1/4"		100	-	1000
PD38F10	1-1/2"		100	-	1000
PD44F10	1-3/4"	Consetts about nin with flute	100	-	1000
PD47F10	1-7/8"	Smooth shank pin with flute	100	-	1000
PD51F10	2"		100	-	1000
PD57F10	2-1/4"		100	-	1000
PD63F10	2-1/2"		100	-	1000
PD76F10	3"		100	-	1000



Heavy Mechanical Galvanized Drive Pins:

Item No.	Shank Length	Description	Box	Case
PD38FMG	1-1/2"	.300" dia. head145" dia. shank. drive	100	1000
PD51FMG	2"	pin, Heavy mechanical galvanized	100	1000
PD63FMG	2-1/2"		100	1000
PD76FMG	3"	for pressure-treated wood	100	1000



▲ Collated Drive Pins:

Item No.	Shank Length	Description	Box	Case
PDC13K	1/2"	Knurled shank pin with plastic strip	100	1000
PDC19K	3/4"	Kriuned sharik piri with plastic strip	100	1000
PDC19BLB	3/4"	Track pin (black) with plastic strip/bulk	-	1000
PDC19	3/4"		100	1000
PDC22	7/8"		100	1000
PDC27	1"		100	1000
PDC32	1-1/4"	C	100	1000
PDC37	1-1/2"	Smooth shank pin with plastic strip	100	1000
PDC52	2"		100	1000
PDC62	2-1/2"		100	1000
PDC72	2-7/8"		100	1000



Washer Pins:

Item No.	Shank Length	Description	Box	Case
PDW19-19F10	3/4"	Pin with 3/4" diameter metal round washer	100	1000
PDW19-25F10	1"	Pili with 3/4 diameter metal round washer	100	1000
PDW25-19F10	3/4"		100	1000
PDW25-25F10	1"		100	1000
PDW25-32F10	1-1/4"		100	1000
PDW25-38F10	1-1/2"	Pin with 1" diameter metal round washer	100	1000
PDW25-51F10	2"		100	1000
PDW25-63F10	2-1/2"		100	1000
PDW25-76F10	3"		100	1000
PDW25-25F10C	1"	Contractor pin with 1" diameter metal round	100	1000
PDW25-32F10C	1-1/4"	washer	100	1000
PDSW28-76F10	3"	Pin with 28mm dia. square metal washer	100	1000



Angle Clip Pins:

•				
Item No.	Shank Length	Description	Box	Case
PDAC120-25F10	1"	Pin with 125° angle clip	100	1000
PDAC120-25F10B] '	Pin with 125° angle clip/Bulk	-	1000
PDAC120-32F10	1-1/4"	Pin with 125° angle clip	100	1000
PDAC120-32F10B	1-1/4	Pin with 125° angle clip/Bulk	-	1000
PDAC90-25F10	1"	Pin with 90° angle clip	100	1000
PDAC90-25F10B] '	Pin with 90° angle clip/Bulk	-	1000
PDAC90-32F10	1-1/4"	Pin with 90° angle clip	100	1000
PDAC90-32F10B	1-1/4	Pin with 90° angle clip/Bulk	-	1000
PDAC90-38F10	1-1/2"	Pin with 90° angle clip	100	1000







8mm Head, .157" Spiral Knurled Shank Drive Pins

Spiral Knurled Collated Pins:

Item No.	Shank Length	Description	Box	Case	Master Box
DNC157-34SK	3/4"		100	1000	5000
DNC157-78SK	7/8"		100	1000	-
DNC157-100SK	1"	Knurled shank pin with plastic	100	1000	-
DNC157-114SK	1-1/4"	washer	100	1000	-
DNC157-112K	1-1/2"	1 1	100	1000	-
DNC157-158SK	1-5/8"		100	1000	-
DNC157-200SK	2"		100	1000	-

- Designed for fasteneing in both cocrete or steel.
- Compatible with Blue Point BP-361 tool and most other brand magazine tools.
- Also available as single pins (Box: 100; Case: 1000)

8mm Head, .145" Shank Drive Pins

Plain Pins:

Item No.	Shank Length	Description	Box	Case	Master Box
DN13P8K	1/2"		100	1000	5000
DN16P8K	5/8"	Kurled shank with plastic washer	100	1000	5000
DN19P8K	3/4"	1	100	1000	5000
DN22P8	7/8"		100	1000	5000
DN27P8	1"		100	1000	-
DN32P8	1-1/4"		100	1000	-
DN37P8	1-1/2"	With plastic washer	100	1000	5000
DN52P8	2"		100	1000	5000
DN62P8	2-1/2"		100	1000	5000
DN72P8	2-7/8"		100	1000	5000



Top Hat Pins:

Item No.	Shank Length	Description	Box	Case	Master Box
DNTH16P8K	5/8"	Knurled shank with plastic washer	100	1000	5000
DNTH22P8	7/8"	\A/ith plactic weeker	100	1000	5000
DNTH25P8	1"	With plastic washer	100	1000	-



Collated Drive Pins:

Item No.	Shank Length	Description	Box	Case
DNC13K	1/2"	Knurled shank with plastic strip	100	1000
DNC19K	3/4"	Khuneu sharik with plastic strip	100	1000
DNC19	3/4"		100	1000
DNC22	7/8"		100	1000
DNC27	1"	ĺ	100	1000
DNC32	1-1/4"	Currently about with wheeting atria	100	1000
DNC37	1-1/2"	Smooth shank with plastic strip	100	1000
DNC52	2"		100	1000
DNC62	2-1/2"		100	1000
DNC72	2-7/8"		100	1000



Angle Clip Pins:

Item No.	Shank Length	Description	Box	Case
DNACTH90-27P8	1"	With Top hat and 90° angle clip	100	1000
DNACTH90-32P8	1-1/4"	With Top hat and 90° angle clip	100	1000



.300" Dia. Head, .145" Dia. pin w/ Conduit Clip

Conduit Clip Pins:

Item No.	Shank Length	Description	Box	Case
CC25-P25	1"	With 1/4" conduit clip	100	1000
CC38-P25	1"	With 3/8" conduit clip	100	1000
CC50-P25	1"	Mith 1/2" conduit alin	100	1000
CC50-P32	1-1/4"	With 1/2" conduit clip	100	1000
CC75-P25	1"	With 3/4" conduit clip	50	500
CC75-P32	1-1/4"	Willi 3/4 Conduit clip	50	500
CC100-P25	1"	With 1" conduit clip	50	500
CC100-P32	1-1/4"	with a conduit clip	50	500





Threaded Studs

1/4"-20 threaded studs:

Item No.	Thread Length	Shank Length	Description	Box	Case
M1/4-19-13D12K		1/2"		100	1000
M1/4-19-25D12	3/4"	1"	With 1/2" plastic and metal washer	100	1000
M1/4-19-32D12		1-1/4"		100	1000
M1/4PH-13-13F10		1/2"		100	1000
M1/4PH-13-25F10	1/2"	1"		100	1000
M1/4PH-19-13F10K		1/2"	With .300" thread cap and rubber flute	100	1000
M1/4PH-19-25F10	3/4"	1"		100	1000
M1/4PH-19-32F10		1-1/4"		100	1000







3/8"-16 Threaded Studs:

Item No.	Thread Length	Shank Length	Description	Box	Case
M3/8-32-16F10K		5/8"k	With rubber flute	100	1000
M3/8-32-19F10K	1-1/4"	3/4"k		100	1000
M3/8-32-25F10		1"		100	1000
M3/8-32-32F10		1-1/4"		100	1000



Other Drive Pins

5.7mm Dia. Head, .145" Dia. Shank Drive Pins:

Item No.	Shank Length	Description	Box	Case	Master Box
NK16W12K	5/8"		100	1000	5000
NK19W12K	3/4"		100	1000	5000
NK22W12K	7/8"		100	1000	5000
NK27W12	1"		100	1000	5000
NK32W12	1-1/4"	With 1/2" metal washer	100	-	1000
NK37W12	1-1/2"	With 1/2 metal washer	100	-	1000
NK42W12	1-5/8"		100	-	1000
NK52W12	2"		100	-	1000
NK57W12	2-1/4"		100	-	1000
NK72W12	2-7/8"		100	-	1000



Timber Clip Pin:

Item No.	Shank Length	Description	Box	Case
TBC250		.312" Diameter Head, .172" diameter shank timber pin with 125° angle clip	100	1000



ANTFAST™ Drive Pins

Drive Pins:

Item No.	Shank Length	Description	Box	Case	Master Box
PD13FKE	1/2"	.300 head, .145" dia. shank, contractor knurled pin w/rubber flute	100	1000	5000
PD25F10E	1"		100	1000	5000
PD32F10E	1-1/4"		100	-	5000
PD38F10E	1-1/2"	.300 head, .145" dia. shank, contractor	100	-	5000
PD51F10E	2"	pin w/flute	100	-	5000
PD63F10E	2-1/2"		100	-	5000
PD76F10E	3"		100	-	5000





Washer Pins:

Item No.	Shank Length	Description	Box	Case
PDW25-25F10E	1"		100	1000
PDW25-32F10E	1-1/4"	.300 head, .145" dia. shank, contractor pin w/1" washer	100	1000
PDW25-38F10E	1-1/2"		100	1000
PDW25-51F10E	2"		100	1000
PDW25-63F10E	2-1/2"		100	1000
PDW25-76F10E	3"		100	1000



Angle Clip Pins:

Item No.	Shank Length	Description	Box	Case
PDAC120-25F10E	1"	.300 head, .145" dia. shank, contractor	100	1000
PDAC120-32F10E	1-1/4"	pin with 125° angle clip	100	1000
PD32CXE	1-1/4"	.300 head, .145" dia. shank, contractor pin w/ XP clip	100	1000





Nitro Ninja Tool



Technical Data:

Fastener Type: Nitro Ninja pins;

Fastener Length: 3/4" - 1-7/8"

Pretied Wires with Nitro Ninja pins

Weight: 3.25 lbs

Length: 16-3/4"

"Excellent holding values in hard concrete"

NT2001 on Pole for Ceiling Applications

Special Features

- No Lead
- Low Noise
- Low Failure Rate
- No Piston
- Low Kickback
- Low Maintenance
- Narrow Profile
- High Pressure Concrete Post Tension Slabs
- Pre-tied Wire Straight Pins Angle Clips Threaded Rod Clips - Conduit Clamps - Zip Tie Clips



Overhead (Ceilings) - Floor - Wall fastening

NT2001



NT2001 with Handle

for Wall & Floor Applications



NT2001 Kit

Item No.	Description	Quantity
NT2001	NT2001 Tool	1
NT2001-17	Handle	1
NT2001-18	Extension Pole	1



Item No. Description	
NJB1	Fastening tool bag w/ compartments & shoulder strap 16.5"x8.0"x9.0"









.300" Dia. Head, .157" Dia. Shank Nitro Ninja Drive Pins:

Plain Pins:

Item No.	Description	Jar/ Box	Case
PD157-12NB/ PD157-12NR	.157 dia. shank, 1/2" shank lgth nitro pin (black/ red)	500	-
PD157-34NB/ PD157-34NR	.157 dia. shank, 3/4" shank lgth nitro pin (black/ red)	500	5000
PD157-100NB/ PD157-100NR	.157 dia. shank, 1" shank lgth nitro pin (black/ red)	500	5000
PD157-114NB/ PD157-114NR	.157 dia. shank, 1-1/4" shank lgth nitro pin (black/ red)	500	5000
PD157-112NB/ PD157-112NR	.157 dia. shank, 1-1/2" shank lgth nitro pin (black/ red)	500	5000





Angle Clip Pins:

Item No.	Description	Jar	Case
PD157-78HNCNB/ PD157-78HNCNR	.157 dia. shank, 7/8" shank lgth top hat nitro pin (black/ red) w/NJ clip	100	1000
PD157-100HNCNB/ PD157-100HNCNR	.157 dia. shank, 1" shank lgth top hat nitro pin (black/ red) w/NJ clip	100	1000
PD157-114HNCNB/ PD157-114HNCNR	.157 dia. shank, 1-1/4" shank lgth top hat nitro pin (black/ red) w/NJ clip	100	1000



Conduit Clip Pins:

Item No.	Description	Jar	Case
PD157-100NR/CC38	3/8" conduit clip w/ .157" dia. shank, 1" nitro pin (red)	100	1000
PD157-100NR/CC50	1/2" conduit clip w/ .157" dia. shank, 1" nitro pin (red)	100	1000
PD157-100NR/CC75	3/4" conduit clip w/ .157" dia. shank, 1" nitro pin (red)	100	600
PD157-100NR/CC100	1" conduit clip w/ .157" dia. shank, 1" nitro pin (red)	100	600



Z Clip Pins:

Item No.	Description	Jar	Case
PD157-100NR/ZC25	1/4" thread Z clip w/.157" dia. shank, 1" nitro pin (red)	100	1000



▲ Conduit Clamp Pins:

Item No.	Description	Jar	Case
PD157-100NR/CP38	3/8" conduit clamp w/ .157" dia. shank, 1" nitro pin (red)	100	1000
PD157-100NR/CP50	1/2" conduit clamp w/ .157" dia. shank, 1" nitro pin (red)	100	1000
PD157-100NR/CP75	3/4" conduit clamp w/ .157" dia. shank, 1" nitro pin (red)	100	600
PD157-100NR/CP100	1" conduit clamp w/ .157" dia. shank, 1" nitro pin (red)	100	600



Pretied Wires with Nitro Ninja Pins:

Item No.	Description
Wxx+4/157-78HNCN	NJ clip w/.157" dia. shank, 7/8" shank lgth top hat nitro pin prettied 12 gauge wire of any length
Wxx+4/157-100HNCN	NJ clip w/.157" dia. shank, 1" shank lgth top hat nitro pin prettied 12 gauge wire of any length
Wxx+4/157-114HNCN	NJ clip w/.157" dia. shank, 1-1/4" shank lgth top hat nitro pin prettied 12 gauge wire of any length

▲ Available on Request

BP-27C POWDER ACTUATED TOOL

.27cal Powder Actuated Ceiling Tool BP-27C



Overhead Hanging Applications

Features and Benefits

• Slim tool. Fits in tight spaces.





- For use in Acoustical, Electrical and Mechanical overhead applications.
- Compatible with Bluepoint Ninja Pole System.
- Uses standard .27 cal. 10 shot strip loads.

Technical Data

Dimensions: 13-3/4" x 6" x 1-1/2"

Weight: 3.0lb Fastener length: 1/2" - 1-1/4"

Load Type: .27cal. (6.8 x 11mm) 10 strip loads
Power Level: Brown/2, Green/3, Yellow/4, Red/5

Item No.	Description
BP-27C	.27cal. Strip powder actuated fastening ceiling tool.



.27cal long strip loads





Item No.	Description
NJB1	Fastening tool bag w/ compartments & shoulder strap 16.5"x8.0"x9.0"

Fasteners & Assemblies

.300" Dia. Head (PD series), .157" & .145" Dia. Shank Drive Pins and Assemblies

8mm Head (DN series), .145" Dia. Shank Drive Pins and Assemblies





Light Weight Heavy Duty Multi-function Ceiling Poles

Item No.	Description	Adjustable length	Weight (Lbs)
PM48	Light Weight Heavy duty adjustable multifunction ceiling pole (MAGNESIUM) w/ rubber grip	4' to 8'	2.5
PM412		4' to 12'	3.4
PM612		6' to 12'	3.4
PM618		6' to 18'	4.7
PM816		8' to 16'	4.2
PM824		8' to 24'	6.0









NINJA ACOUSTIC POLE ADAPTER SYSTEMS



Light Weight Heavy Duty Multi-function Ceiling Poles


PATENTED



Features and Benefits:

- Stackable
- Fits Viper™ (I, II, III), Sniper, Nitroset™ and Ninja forced entry ceiling tool systems
- Fits Viper™ IV with an NPA4 adapter (See page 16)
- Most trigger operated PAT tools can be utilized with push actuated saddle (See page 16)
- Multiple attachment configurations on the same pole makes you and your crew more productive

Item No.	Description	Adjustable length	Weight (Lbs)
PM48	Light Weight Heavy duty adjustable multifunction ceiling pole (MAGNESIUM) w/ rubber grip	4' to 8'	2.5
PM412		4' to 12'	3.4
PM612		6' to 12'	3.4
PM618		6' to 18'	4.7
PM816		8' to 16'	4.2
PM824		8' to 24'	6.0









Lag-Pro Magnesium Multi-function Poles

Item No.	Description	Adjustable length	Weight (Lbs)
PM48L	Light Weight Heavy duty adjustable multifunction ceiling lag pole (MAGNESIUM) w/ rubber grip	4' to 8'	2.5
PM412L		4' to 12'	3.4
PM612L		6' to 12'	3.4
PM618L		6' to 18'	4.7
PM816L		8' to 16'	4.2
PM824L		8' to 24'	6.0





Lag-Pro Aluminum Poles

Features and Benefits:

- Used to install threaded rods, ceiling wires, jack chain, pretied wires etc. to a variety of ceiling structures
- · Best cost performance in the market
- This pole can be stacked with our Multi-function ceiling pole

Item No.	Description	Adjustable length	Weight (Lbs)
P48L	Lag-Pro Aluminum Adjustable Ceiling Pole Directly comparable with all competitors tools and adapters	4' to 8'	3.5
P412L		4' to 12'	4.5
P612L		6' to 12'	4.5
P618L		6' to 18'	5.9
P816L		8' to 16'	7.4
P824L		8' to 24'	10.4







NINJA ACOUSTIC POLE ADAPTER SYSTEMS

Acoustic Pole System Adapters





Adapter Kits



Item No.	Description	Include	Qty.
NPAK-1	Ninja Adapter Kit 1 includes the following: • Tie wire wedge anchor installer • Eye lag head • Pretied wire head • Hex drive adapter • Lock pin • Base attachment, 3/8" hex drive • Plastic case	NPDA1 NPA1 NPA2 NPA3 NPLP NPBA2 NPAK-1C	1 1 1 1 1 1
14			


anan da sa

Item No.	Description	Include	Qty.
NPAK-2	Ninja Adapter Kit 2 includes the following: • Tie wire wedge anchor Installer • Eye lag head • Pretied wire head • Hex drive adapter • Connection adapter for Viper 4™ • Drill chuck adapter • Lock pin • Base attachment, 3/8" hex drive • Plastic case	NPDA1 NPA1 NPA2 NPA3 NPA4 NPA9 NPLP NPBA2 NPAK- 2C	2 2 2 2 1 1 4 3 1



Item No.	Description
NJB1	Fastening tool bag w/ compartments & shoulder strap 16.5"x8.0"x9.0"

* All adapters have 3/4"-16 SAE threads





Adapternoint		
Item No.	Description	
NPA1	Eye lag head	
NPA2	Pre-tied wire head adapter	
NPA3	Hex drive adapter	
NPA4	Connection adapter used with Viper 4 ™ PAT Tool	
NPBA2	Base attachment, 3/8" hex drive	
NPPCI	Purlin clip installation tool for PC25 and PCZ25 clips	

Adapters










Item No.	Description
NPDA1	Tie Wire Anchor Installer
NPLP	Lock Pin
NPA9	Drill Chuck Adapter
NPAFT	PAT Pole Saddle Head 2 Fits to: • Blue Point® BP-301C, BP-302A, BP-303A, BP-361 • Hilti® DX35, DX350, DX351,DX2 • Simpson® PT-27 • Ramset® Cobra, R25 • Powers® P3500, PA3500, P35s, P3600



Rivets

Features and Benefits

- ° Quick and easy installation from one side of the workpiece
- ° Available in Dome or Countersunk Head
- ° Colored Head match to Pantone, RAL or sample color upon request







Item No.	Description	Diameter	Rivet Length	Bag	Box	Case	
AA42WBULK			0.275"	-	-	10000	
AA42W1000	5052 Aluminum alloy Rivets with aluminum mandrels and WHITE colored Head			0.275"	-	1000	20000
AA42W100			0.275"	100	1000	12000	
AA44WBULK			0.4"	-	-	10000	
AA44W1000		1/8"	0.4"	-	1000	20000	
AA42B1000	5052 Aluminum alloy Rivets with aluminum mandrels		0.275"	-	-	10000	
AA42BBULK			0.275"	-	1000	20000	
AA44BBULK	and BLACK colored Head		0.4"	-	-	10000	
AA44B1000			0.4"	-	1000	20000	



TEE-Locator (Item# TL)





Fig. 3

.

Instructions for use:

- TEE-LOCATOR is designed to be used with either 9/16" or 15/16" gridwork (Fig. 1.).
- ° Place the TEE-LOCATOR as shown in Fig. 2 or 3. The magnets will ensure that it sticks to the Gridwork. Be sure that the long leg is pointed to the wall to ensure it is at a 90 degree angle.
- The Cross-Tee will now be square to the wall and you can punch a hole through the Wall Angle and Cross-Tee before fastening it in place with a rivet.
- ° Remove TEE-LOCATOR from the Grid.

Riveters



HR-702 Hand Riveter (In 2 jaws)



HR-705 Hand Riveter (In 2 jaws) (up to 3/16" for all material)



HR-708 Hand Riveter (In 3 jaws) (up to 3/16" for all material)



*Exclusive manufacturer of both PAT and Gas tools for insulation as teners EPO INT

Insulation FasteningTools:

BP-361N



BP-303N



GT-120N





▲ Available on Request



Powder Loads:


Item No.	Item No. Color	
27LS11L6	Black	6
27LS11L5	Red	5
27LS11L4	Yellow	4
27LS11L3	Green	3



.27 cal. Low Velocity Insulation Loads

IF60-125-158S





Insulation Washers:

	Item No.	Description	Insulation Thickness	Penetration Length	Bag	Case
	IF60-125-158S		1"-1 1/4"	1"	50	1000
l e	IF60-150-158S		1 1/2"	1"	50	
ᇤ	IF60-200-200S	.300" Dia. head, .145"157"	2"	1"	50	900
CONCRETE	IF60-300-200S	step shank pin with 60mm dia. insulation washer.	3"	1"	50	600
8	IF60-400-200S		4"	1"	50	500
For	IF60-500-200S		5"	1"	25	300
	IF60-600-200S		6"	1"	25	300
	IF60-125-158K		1"-1 1/4"	1"	50	1000
١.	IF60-150-158K		1 1/2"	1"	50	
METAL	IF60-200-200K	.300" Dia. head, .157" knurled	2"	1"	50	900
뿔	IF60-300-200K	shank pin with 60mm dia. insulation washer(For metal studs, light metal frame etc.).	3"	1"	50	600
For	IF60-400-200K		4"	1"	50	500
	IF60-500-200K	stade, light metal frame etc.).	5"	1"	25	400
	IF60-600-200K	1	6"	1"	25	300

PDIW36-38F10



* Metal Washer

PIWP112G



* Gray Plastic Washer

PIWP112W



* White Plastic Washer

Membrane Washer Pins:

Item No.	Description	Shank Dia.	Shank Length	Вох	Case
PDIW36-38F10	000" " 445" "	.145"	1-1/2"	100	1000
PDIW36-51F10	.300" dia. head, .145" dia. shank drive pin w/ 36mm dia. metal	.145"	2"	50	500
PDIW36-63F10	round insulation washer	.145"	2-1/2"	50	500
PDIW36-76F10	Tourid Insulation Washer	.145"	3"	50	500
PIWP112G	.300" dia. head, .145" dia. shank	.145"	1-1/2"	100	1000
PIWP112W	drive pin w/ 36mm dia. plastic	.145"	1-1/2"	100	1000
PIWP212W	round insulation washer	.145"	2-1/2"	100	1000





Pretied Ceiling Wire

- ° ICC-ES ESR-1530 certified pins
- Meets or exceeds wire standards ASTM A641-92
- ° All wires are tied with the hospital wrap
- Tie requirement to ensure maximum holding power as dictated by building code
- ° Wire gauge:8 thru 12 gauge
- ° Length:2', 4', 6', 8', 10', 12', 14', 16', 18', 20' available
- ° Custom lengths also available
- Multiple wire termination options(see below)
- Wire can be purchased by:
 - a) Container for maximum savings
 - b) Bundles of 100pcs capped and wrapped securely
 - c) Master bundles of 20-100pc bundles
 - d) Steel crates that are stackable

DiameterTensile RangeZinc Thickness0.105"75ksi max≥25g/m2

Straight Cut Wires:



Coiled Wire:

Technical Data - 12 gauge wire



Hospital Tied


8 & 9 Gauge Tied


12 Gauge Double Tied



Steel Crate Quantity

Bundles / Steel crate						
Wire length 4"	160 bdls					
Wire length 6"	140 bdls					
Wire length 8"	120 bdls					



























	Part No.	Description	Вох	Case
	TWM1A	Electric EZ wire tie machine/ 110V (for 12 gauge wire)	1	1
	TWM3	Electric EZ wire tie machine/ 230V (for 8 and 9 gauge wire)	1	1

WIRE HANGING SYSTEMS



Wire Attachment Options							
	Product	Part No.	Description	Вох	Case		
		EL200W	2" wood eye lag wood screw/ plain	100	1000		
	wannau unannannan .	EL300W	3" wood eye lag wood screw/ plain	100	1000		
		EL300WB	3" wood eye lag wood screw/ plain/ Bulk	-	1000		
ĺ		EL300WZ	3" wood eye lag wood screw/ white zinc	100	1000		
	- diamininamy	EL300WZB	3" wood eye lag wood screw/ white zinc/ Bulk	-	1000		
*		EL400W	4" wood eye lag wood screw/ plain	100	1000		
^		EL400WB	4" wood eye lag wood screw/ plain/ Bulk	-	1000		
*		EL500W	5" wood eye lag wood screw/ plain	100	1000		
		EL500WB	5" wood eye lag wood screw/ plain/ Bulk	-	1000		
		EL75SD	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, yellow zinc self-drilling. Used for 16 to 22 gauge sheet metal.	100	1000		
		EL75SDB	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, yellow zinc self-drilling. Used for 16 to 22 gauge sheet metal.	-	1000		
		EL75SDZ	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, white zinc self-drilling. Used for 16 to 22 gauge sheet metal.	100	1000		
		EL75SDZB	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, white zinc self-drilling. Used for 16 to 22 gauge sheet metal.	-	1000		
*	5/16" BIG HOLE	EL75BSD	2" overall lgth, ~1/2" thread lgth, 3/4" from collar to self drill point, 5/16" Eye. Used for 16 to 22 gauge sheet metal.	100	1000		
*		EL150SP	2-3/4" overall lgth, ~ 1-1/2" thread lgth. Sharp point. Used for 20 to 22 gauge metal decking and also in wood applications.	100	1000		
*		EL200SD	3-1/4" overall lgth,~1-3/4" threaded lgth, 2" from collar to drill point. Used for 16 to 22 gauge sheet metal.	100	1000		
		EL100DSD	2-1/4" overall lgth, 1" from collar to drill point, Deep Drilling eye lag screw, Blue Ruspert finish. Extra Wide tool tip enables it to be used for up to 1/4" thick structural steel.	100	1000		
	watahana.	EL14114	2-1/2" overall length, Concrete Eye Lag Screw, Blue Ruspert finish. High-low thread, thread lgth 1-1/4".	100	1000		
		TWA14114	1/4" x 1-1/4" Tie wire wedge anchor	100	1000		
A		TWA14200	1/4" x 2" Tie wire anchor	100	1000		
		TWSP14114	1/4" x 1-1/4" Tie wire spike pin anchor	100	1000		
_		TWSP316114	3/16" x 1-1/4" Tie wire spike pin anchor	100	1000		
A		TWSA14114	1/4" x 1-1/4" Tie wire split drive anchor	100	1000		
		HBC25	Hammer-on beam clamp (1/8" - 1/4")	100	1000		
		HBC50	Hammer-on beam clamp (5/16" -1/2")	100	1000		
		PCZ25	Z-Purlin clip (1/8" -1/4")	100	1000		
İ	4	PC25	C-Purlin clip (1/8" - 1/4")	100	1000		
	1	AC90	14 gauge 90 degree angle clip Holes Ø5.5mm & Ø8mm	100	1000		
		AB90	12 gauge heavy duty clip, 90 degree Holes Ø5.2mm & Ø10.5mm	100	1000		
		AB45	12 gauge heavy duty clip, 45 degree Holes Ø5.2mm & Ø10.5mm	100	1000		

- ▲ Available on Request ※ Bright Zinc Plating Available on Request



Toggle Bolts

Product	Item No.	Description	Weight Lbs./Case	Package
A second	TBA14414	1/4"-20 * 4-1/4" zinc plated tog- gle bolt, with 1-1/2" metal washer assembled	9.2	100 pcs/box, 6 boxes/carton
- Carrent -	TBSA14500	1/4"-20 * 5" zinc plated toggle bolt, with 1-1/2" metal washer & spring assembled	10.8	100 pcs/box, 6 boxes/carton

Wood Screws

Product	Item No.	Description	Вох	Lbs./ Box	Case
\$4400000000000000000000000000000000000	EL200W	2" eye lag wood screw/ plain	100	1.50	1000
	EL300W	3" eye lag wood screw/ plain	100	2.20	1000
	EL300WB	3" eye lag wood screw/ plain/ Bulk	1	-	1000
Single for the light lig	EL300WZ	3" eye lag wood screw/ white zinc	100	2.20	1000
C MANUFACTURE AND ASSESSED FOR THE PARTY OF	EL300WZB	3" eye lag wood screw/ white zinc/ Bulk	1	-	1000
	EL400W	4" eye lag wood screw/ plain	100	2.98	1000
	EL400WB	4" eye lag wood screw/ plain/ Bulk	1	-	1000
	EL500W	5" eye lag wood screw/ plain	100	3.81	1000
***************************************	EL500WB	5" eye lag wood screw/ plain/ Bulk	-	-	1000

Eye Lag Screws

	Product	Item No.	Description	Вох	Lbs./ Box	Case
*		EL75SD	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, yellow zinc self-drilling. Used for 16 to 22 gauge sheet metal.	100	1.92	1000
**		EL75SDB	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, yellow zinc self-drilling. Used for 16 to 22 gauge sheet metal.	-	-	1000
		EL75SDZ	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, white zinc self-drilling. Used for 16 to 22 gauge sheet metal.	100	1.92	-
		EL75SDZB	2" overall lgth, 1/2" thread lgth, 3/4" from collar to drill point, white zinc self-drilling. Used for 16 to 22 gauge sheet metal.	-	-	1000
▲ ※	5/16" BIG HOLE	EL75BSD	2" overall lgth, ~1/2" thread lgth, 3/4" from collar to self drill point, 5/16" Eye. Used for 16 to 22 gauge sheet metal.	100	1.92	1000
*		EL150SP	2-3/4" overall lgth, ~ 1-1/2" thread lgth. Sharp point. Used for 20 to 22 gauge metal decking and also in wood applications.	100	2.74	1000
*		EL200SD	3-1/4" overall lgth,~ 1-3/4" threaded lgth, 2" from collar to drill point. Used for 16 to 22 gauge sheet metal.	100	3.04	1000
		EL100DSD	2-1/4" overall lgth, 1" from collar to drill point, Deep Drilling eye lag screw, Blue Ruspert finish. Extra Wide tool tip enables it to be used for up to 1/4" thick structural steel.	100	2.20	1000
	polititititititititi	EL14114	2-1/2" overall lgth, Concrete Eye Lag Screw, Blue Ruspert finish. High-low thread, thread lgth 1-1/4".	100	2.30	1000

Super Screw for Concrete, Wood and Steel

Product	Item No.	Description	Вох	Case
	2520RC150SP	1/4-20 rod coupling, point to collar 1-1/2" lgth, heat treated screw, non-detachable hex coupling	100	1000
	3816RC150SP	3/8-16 rod coupling, point to collar 1-1/2" lgth, heat treated screw, non-detachable hex coupling	100	1000
	2520RC75SD	1/4-20 rod coupling, point to collar 3/4" lgth, self-drilling, heat treated screw, 16 to 22ga. Sheet metal, non-detachable hex coupling		1000
	3816RC200SP	3/8-16 rod coupling with 2" sharp point screw,	100	1000

HOOKS/ HANGERS



Attachments

Item No.	Description	Вох	Lbs./Box
BR10-75	Bridle Ring 10-24 X 3/4"	100	3.31
BR10-200	Bridle Ring 10-24 X 2"	100	6.17
BR25-125	Bridle Ring 1/4"-20 X 1-1/4"	100	7.28
BR25-200	Bridle Ring 1/4"-20 X 2"	100	10.36



	Part No.	Description	Вох	Lbs./ Case	Case
	PC25	C-Purlin clip 1/8"-1/4"	100	5.60	1000
	PCZ25	Z-Purlin clip 1/8"-1/4"	100	4.20	1000
	HBC25	Hammer-on beam clip 1/8"-1/4"	100	3.03	1000
	HBC50	Hammer-on beam clip 5/16"-1/2"	100	3.58	1000
	BC50	Beam clamp w/ two 1/4"-20 holes, for flanges up to 1/2" thick	100	11.64	1000
Ç	BCS50	Beam Clamp (Spring steel) w/ 1/4"-20 hole, for flanges up to 1/2" thick	100	5.19	1000
	PC25-EC25	1/8"-1/4" Purlin Clip w/ 1/4"-20 Eye Coupling	100	7.72	1000
	PC25-EC38	1/8"-1/4" Purlin Clip w/ 3/8"-16 Eye Coupling	100	11.55	1000
	PCZ25-EC25	1/8"-1/4" Z-Purlin Clip w/ 1/4"-20 Eye Coupling	100	6.33	1000
	HBC25-EC25	1/8"-1/4" Beam Clip w/ 1/4"-20 Eye Coupling	100	5.16	1000
	HBC50-EC25	5/16"-1/2" Beam Clip w/ 1/4"-20 Eye Coupling	100	5.71	1000
	BW25	Bat-Wing clip for 1/4" rod and 12 gauge wire	100	2.84	1000

	Part No.	Description	Вох	Lbs./ Case	Case
Ţ.	ZC25-P32	Z clip (w/ 1/4" threaded hole) w/ .145" shank dia., 1-1/4" shank lgth. pin	100	4.41	1000
	ZC25-P157-100	Z clip (w/ 1/4" threaded hole) w/ .157" shank dia., 1" shank lgth. pin	100	4.41	1000
	ZC25	Z clip (w/ 1/4" threaded hole)	100	3.68	1000
	EC25-AC90	Eye Coupling (1/4"-20) with 90 degree angle clip	100	5.00	1000
	EC25-ACP32	Eye Coupling (1/4"- 20) with 90 degree angle clip pin (.145 shank dia., 1-1/4" shank lgth.)	100	5.46	1000
D 111-6	RH3 RH3	Dual thread rod hanger (1/4"-20 & 3/8"-16)	100	6.89	1000
437-6	N100RH2	Dual thread rod hanger (1/4"-20 & 3/8"-16) w/ 1" lgth. shank NJ pin	100	8.20	1000
	N125SRH2	Dual thread rod hanger (1/4"-20 & 3/8"-16) w/ 1-1/4" shank lgth. NJ pin	100	8.33	1000
	PD157-100RH1	Dual thread rod hanger (1/4"-20 & 3/8"-16) w/ .157" shank, 1" lgth. pin	100	8.20	1000
	PD157-125RH1	Dual thread rod hanger (1/4"-20 & 3/8"-16) w/ .157" shank dia., 1-1/4" shank lgth. pin	100	8.32	1000
8	EC25	Eye coupling 1/4"-20	100	2.12	1000
	EC38	Eye coupling 3/8"-16	100	5.95	1000
130	AC90	14 gauge 90 degree angle clip	100	2.87	1000



Rod Hangers



Part No.	Description	
THI4	Rod hanger for 1/4" threaded rod, with thread impression	100
THI6	Rod hanger for 3/8" threaded rod, with thread impression	100

Flange Mounted Conduit Clips



Part No.	Description	Вох
HFC24CC6	3/8" MC/AC cable to 1/8" to 1/4" flange	100
HFC58CC6	3/8" MC/AC cable to 5/16" to 1/2" flange	100
HFC912CC6	3/8" MC/AC cable to 9/16" to 3/4" flange	100
HFC24CC812	1/2" or 3/4" hammer-on pipe clip for flanges 1/8"-1/4"	100
HFC58CC812	1/2" or 3/4" hammer-on pipe clip for flanges 5/16"-1/2"	100
HFC912CC812	1/2" or 3/4" hammer-on pipe clip for flanges 9/16"-3/4"	100
HFC24CC16	1" hammer-on Pipe clip for flange 1/8"-1/4"	100
HFC58CC16	1" hammer-on Pipe clip for flange 5/16"-1/2"	100
HFC912CC16	1" hammer-on Pipe clip for flange 9/16"-3/4"	100
HFC24CC20	1-1/4" hammer-on Pipe clip for flange 1/8"-1/4"	100
HFC58CC20	1-1/4" hammer-on Pipe clip for flange 5/16"-1/2"	100
HFC912CC20	1-1/4" hammer-on Pipe clip for flange 9/16"-3/4"	50
HFC24CC24	1-1/2" hammer-on Pipe clip for flange 1/8"-1/4"	50
HFC58CC24	1-1/2" hammer-on Pipe clip for flange 5/16"-1/2"	50
HFC912CC24	1-1/2" hammer-on Pipe clip for flange 9/16"-3/4"	50
HFC24CC32	2" hammer-on Pipe clip for flange 1/8"-1/4"	50
HFC58CC32	2" hammer-on Pipe clip for flange 5/16"-1/2"	50
HFC912CC32	2" hammer-on Pipe clip for flange 9/16"-3/4"	50



Part No.	Description	Вох
HFC24	Hammer-on flange clip, FT 1/8" to 1/4", bottom mount	100
HFC58	Hammer -on flange clip, FT 5/16" to 1/2", bottom mount	100
HFC96	Hammer -on flange clip, FT 9/16" to 3/8", bottom mount	100



Part No.	Description	Вох
HFC24S	Hammer-on flange clip with 1/4"x3/8" stud for 1/8-1/4" flanges	100
HFC58S	Hammer-on flange clip with 1/4"x3/8" stud for 5/16-1/2" flanges	100
HFC96S	Hammer-on flange clip with 1/4"x3/8" stud for 9/16-3/8" flanges	100

HOOKS / HANGERS/ J-HOOKS





















▲ Available on Request